



- Semi Synthetic
- Diesel Engine Oil
- High Total Base Number



Camel Super Turbo Diesel Engine Oil is the premium choice for API CI-4 / SL, ACEA E7 - 16 emission - quality diesel oil required by model 2010 and newer diesel engines. It delivers extraordinary lubrication in diesel engines found in commercial, fleet and personal vehicles.

It exceeds the higher performance demands of modern engines. It withstands the stress of the heat, soot and acid to help prevent deposits, wear and corrosion. It is wax free and it resist breakdown and offers maximum fuel efficiency over extended drain intervals.

Highest Quality Additive Technology. All Calcium Detergent Chemistry. Low Volatility. Long Drain TBN Retention. Low Oil Consumption, High Lubricity. Excellent Wear Protection.

Provides Improved Fuel Economy. Excellent Heat Resistance. 100% Shear Stable Improver. Suitable For Long Oil Change Intervals. Highest Quality Synthetic Blend.

CHARACTERISTICS

15W40

15W50

20W50

Sp. Gravity @ 15°C

0.880

0.885

0.83

Viscosity @ 40°C, cSt

110

151.45

170

Viscosity @ 100°C, cSt

14.5

18.5

19

Viscosity Index

135

130

130

Flash Point, COC, °C

220

240

240

Pour Point, °C

-33

-30

-27

TBN, mgm KOH/gm

11.5

11.5

11.5