



- Excellent thermal
- Outstanding shear stability
- Extends component life

Gear Lubricant is designed for high horsepower, high torque conditions. Made from the highest quality heavy synthetic base oils, Gear Oils contain a extreme pressure lubricants specially engineered for shear stability and the demands of severe racing conditions. This synthetic formulation provides a barrier cushion between metal surfaces. It absorbs impact by creating a barrier coating on gear surfaces for the critical line of protection against wear, pitting & scoring. This oil is long lasting and perfect for any heavy duty application.

Gear oil is designed for the Top Fuel & the off-road industry. Outstanding resistance to oxidation and thermal degradation, Reduced deposits and coking, extended service life with the potential for reduced maintenance. Potent anti-wear protection, Can help reduce compressor component wear and thereby reduce maintenance requirements. Excellent rust and corrosion protection. Internal components are protected from surface degradation, thereby extending component life.

Rapid release of foam and air, protecting components from aeration and cavitation damage, leading to reduced wear. Rapid water separation from the oilless carryover to downstream equipment.

CHARACTERISTICS

ISO VG 220

ISO VG 320

ISO VG 460

Sp. Gravity @ 15°C

0.910

0.890

0.910

Viscosity @ 40°C, cSt

210

305

465

Viscosity @ 100°C, cSt

20.70

27.5

42

Viscosity Index

115

120

140

Flash Point, COC, °C

248

250

250

Pour Point, °C

-24

-21

-21